

▼ Shown from left to right: WHC-3380, WHC-750



WHC, WHR, STC Series

Capacity:
3 - 20 ton

Cutting Capacity:
12 - 101 mm


Maximum Operating Pressure:
700 bar

Replacement Blades

To order 60-62HRC hardened replacement blades use one of the model number shown below.

For Cutter Model Number	Order Blades Modelnr.
WHC-750	WCB-750
WHC-1250	WCB-1250
WHC-2000	WCB-2000
WHC-3380	WCB-3380
WHC-4000	WCB-4000
WHR-1250	WCB-1250

- Single-acting, spring return on all models, except WHR-1250
- Guillotine action for easy operation
- Lifting handles on larger models for easy transport
- Carrying bag included for easy carrying and tool protection
- Ideal for use with most Enerpac pumps featuring 3-way valve or dump valve and 700 bar pressure rating (except WHR-1250, which requires 4-way valve)
- CR-400 coupler and dust cap included on all models



Tool Sets

Cutterheads marked with an * are available as sets (pump, tool, gauge, couplers and hose) for your ordering convenience.

Cutterhead Modelnr.	Pump Modelnr.	Set Model Number
WHC-750	P-392	STC-750H
WHC-750	PATG-1102N	STC-750A
WHC-1250	P-392	STC-1250H
WHC-1250	PATG-1102N	STC-1250A

▼ Selection Chart Maximum Cutting Capacities (ø in mm)

Cutter Head Operation	Capacity ton	Model Number	Oil Capacity (cm ³)	Length (mm)	Steel Wire Rope, Hemp-core or IWRC 6x7 6x12 6x19	Round Bar				Wire Strand			Cable		⚠ (kg)	
						Copper Wire or Bar	Aluminium Wire or Bar	Soft Steel Bolts	Reinforcing Bar	Bare Copper Wire Strands	Bare Aluminium Wire Strands	ACSR	Guy Steel Wire Strands	Telephone Cable CPP		Underground Cable (Power)
Single-Acting	4	WHC-750*	19,7	127	19	19	19	19	12	19	19	19	16	☆	☆	3,2
	20	WHC-1250*	134,4	279	31	28	31	28	25	31	31	31	22	☆	☆	11,3
	13	WHC-2000	119,6	381	25	31	31	22	☆	50	50	50	19	☆	50	10,4
	3	WHC-3380	65,5	482	☆	☆	☆	☆	☆	41	42	☆	☆	85	85	9,1
	8	WHC-4000	137,7	609	☆	☆	☆	☆	☆	☆	☆	☆	☆	101	101	14,5
Dbl.-Act.	20	WHR-1250	122,9	419	31	31	31	28	25	31	31	31	22	☆	☆	11,8

* Available in sets with Handpump or Turbo Air Pump.

☆ Will not cut designated material.